BALUX

VESSEL SINK INSTALLATION GUIDE

Recommandations

- **It is recommended to immediately wipe off any product that could cause staining.**
- **Avoid leaving objects on the surface for an extended period, as trapped moisture under these objects could cause damage to the sealer.**
- **It is advised to place something under soap bottles to allow water underneath to dry.**
- **Do not use abrasive or corrosive products, brushes, or sponges that could damage the top layer of the sealer. Be cautious with essential oils and eye contact cleaner as they can damage the sealer.**
- **Do not leave a Balux sink filled with water for a prolonged period.**
- **Sharp objects on the surface may cause scratches and damage the sealer**

Maintenance

- Our products can be cleaned with our **Daily Clean** soap or a mild, non-abrasive, and non-corrosive soap.It is recommended to use **Weekly Clean** once a week to enhance the sealer's durability. stubborn stains.

- If a stain occurs, use bleach and let it sit on the surface for a few minutes, repeating if necessary until the stain disappears. **CLR Bathroom** (yellow bottle) can be used on dark colors to remove water-based limescale stains.Do not use a magic eraser as it will damage the sealer.

- Apply silicone around the underside perimeter of the basin.

- Under the basin, apply silicone around the perimeter of the drain hole.

- Place the basin and apply light pressure to ensure it is evenly supported.

- Ensure that the basin is level.

- Apply a generous amount of silicone in the drain imprint (before installing the drain). Do not use the sealing gasket provided with the drain, as it will make the drain too high and prevent proper water drainage.

- Slide the drain into the imprint and ensure there is enough silicone to properly seal the underside.

- Hand-tighten the drain without over-tightening to avoid pressure that could cause a crack over time

- Feel free to contact us at 438-401-8267 or by email at info@balux.ca.,

BALUX

FICHE TECHNIQUE INSTALLATION VASQUE

Recommandations

- **Il est recommandé d'essuyer immédiatement tout produit susceptible de causer des taches.**
- **Évitez de laisser des objets sur la surface pendant une longue période, car l'humidité emprisonnée sous ceux-ci pourrait endommager le scellant.**
- **Il est conseillé de placer quelque chose sous les bouteilles de savon afin de permettre à l'eau en dessous de sécher.**
- **Ne pas utiliser de produits abrasifs ou corrosifs, ni de brosses ou d'éponges pouvant endommager la couche supérieure du scellant. Faites preuve de prudence avec les huiles essentielles et les nettoyants pour lentilles, car ils peuvent endommager le scellant.**
- **Ne pas laisser un évier Balux rempli d'eau pendant une longue période.**
- **Les objets tranchants sur la surface peuvent provoquer des égratignures et endommager le scellant.**

Entretient

- Nos produits peuvent être nettoyés avec notre savon **Daily Clean** ou avec un savon doux, non abrasif et non corrosif. Il est recommandé d'utiliser **Weekly Clean** une fois par semaine afin d'augmenter la durabilité du scellant.
- En cas de tache, utilisez de l'eau de Javel et laisser agir quelques minutes sur la surface, en répétant au besoin jusqu'a ce que la tache disparaisse. Le produits SCL Salle de Bain (bouteille jaune) peut être utilisé sur les couleurs foncées pour enlever les taches de calcaire d'origine aqueuse. Ne pas utiliser d'éponge magique (magic eraser) car elle endommage le scellant.

✦ En dessous mettre du silicone sur le pourtour de la vasque.

✦ En dessous de la vasque mettre du silicone sur le pourtour du trou de drain.

✦ Déposer la vasque et mettre une légère pression pour s'assurer que la vasque est bien appuyé de façon uniforme.

✦ S'assurer que la vasque est mise au niveau.

✦Mettre généreusement du silicone dans l'empreinte de drain (avant de mettre le drain). Ne pas mettre le joint d'étanchéité fourni avec le drain, cela fait que le drain est trop haut et l'eau ne s'évacuera pas correctement.

✦Glisser le drain dans l'empreinte et s'assurer qu'il y a assez de silicone pour bien sceller le dessous..

✦Serrer le drain a la main sans serrer trop fort pour ne pas causer de pression qui causerait des fissures avec le temps.

✦N'hésiter pas a communiquer avec nous au 438-401-8267 ou par courriel a info@balux.ca